

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A touch fastener product for use as a mold insert, the product comprising:

a resin base having an upper faces and a lower faces and ~~a central portion disposed between lateral selvages, the central portion having a nominal thickness and carrying a plurality of resin fastener elements with stems integrally molded with and extending in an array from the lower face between side edges of the base;~~

a magnetically attractable material secured to ~~an upper face of~~ the base; and

~~a plurality of fastener elements extending in an array from the lower face of the central portion of the base;~~

~~wherein the~~ a film extending across the upper face of the base and laterally beyond the side edges of the base to form lateral selvages comprise a film having a nominal thickness of less than about 0.020 inch and being of a significantly lesser stiffness and thickness than the base stiffness of the central portion of the base, for flexure of the selvages to sealingly conform to a mold surface as the base of the fastener product is drawn towards the mold surface by magnetic attraction of the magnetically attractable material.

2. (Currently Amended) The touch fastener of claim 1 wherein the touch fastener is base and fastener elements are formed of a single contiguous resin.

3. (Currently Amended) The touch fastener of claim 1 wherein the ~~central portion~~
base comprises a strip of a first material supporting the fastener elements, and wherein the
~~selvedges are~~ film is formed of a second material of different composition than the first material.

4. (Cancelled)

5. (Cancelled)

6. (Currently Amended) The touch fastener of claim 5 1 wherein the film is secured
to the upper face of the base by an adhesive.

7. (Original) The touch fastener of claim 6 wherein the adhesive is a polyamide hot
melt.

8. (Original) The touch fastener of claim 5 wherein the film is a polyamide film.

9. (Original) The touch fastener of claim 5 wherein the film has a softening point of
between about 120 and 220 degrees Fahrenheit.

10. (Previously Presented) The touch fastener of claim 5 wherein the film has a
nominal thickness of less than about 0.005 inch.

11. (Original) The touch fastener of claim 10 wherein the film has a nominal
thickness of less than about 0.010 inch.

12. (Original) The touch fastener of claim 10 wherein the film has a flexural rigidity
of about 1800 mg-cm.

13. (Original) The touch fastener of claim 5 wherein the film has a tensile stiffness of between about 1000 and about 3000 mg-cm.

14. (Currently Amended) The touch fastener of claim 1 wherein the nominal thickness of the ~~central portion of the~~ base is between about 0.002 and 0.012 inch.

15. (Currently Amended) The touch fastener of claim 1 wherein the nominal thickness of the ~~central portion of the~~ base is greater than a nominal thickness of the selvages.

16. (Original) The touch fastener of claim 1 wherein the magnetically attractable material comprises a metal wire.

17. (Original) The touch fastener of claim 1 wherein the magnetically attractable material comprises a metal strip.

18. (Original) The touch fastener of claim 1 wherein the magnetically attractable material comprises a coating of magnetically attractable particles.

19. (Original) The touch fastener of claim 1 wherein the magnetically attractable material is encapsulated in a hot melt adhesive.

20. (Currently Amended) The touch fastener of claim 1 wherein each selvedge extends ~~from~~ beyond the ~~array~~ base at least about 2 millimeters.

21. (Currently Amended) The touch fastener of claim 20 wherein each selvedge extends ~~from~~ beyond the ~~array~~ base at least about 4 millimeters.

22. (Original) The touch fastener of claim 1 wherein the ~~selvedges are of a material~~
~~having film~~ has a flexural rigidity of between about 1000 and 3000 mg-cm.

23. (Canceled)

24. (Currently Amended) The touch fastener of claim 1 wherein the ~~central portion~~
~~of the base~~ comprises a molded resin.

25. (Original) The touch fastener of claim 1 wherein the fastener elements are male
fastener elements.

26. (Canceled)

27. (Original) The touch fastener of claim 26 wherein the male fastener elements
have loop-engagable heads molded at distal ends of the stems.

28. (Original) The touch fastener of claim 27 wherein the male fastener elements are
hook-shaped.

29. (Original) The touch fastener of claim 1 wherein the fastener elements are
arranged in a density of at least about 100 per square inch across the array.

30. (Original) The touch fastener of claim 1, the fastener elements having an overall
height, as measured normal to the base, of less than about 0.050 inch.

31-101. (Cancelled)